

Geckolighting® LED IP67 Drivers



Constant Voltage LED Power Supply. MSD Range

- IP67
- PF>0.98
- Protections: Short Circuit/Over Load/Over Voltage/Over Temperature
- Low temperature resistant(-45°C)
- 4000VAC high voltage protection
- Low THD (<15%) and low Ripple (<3%)
- NCC/Rubycon capacitor
- SAA,TUV,ETL,CE, RoHS



IP67 Constant Voltage LED Driver

Order Code	Model No.	Input Voltage	Output Voltage	Current (AMP)	Max Power (W)	Dimensions (MM)	Weight (g)
45-PS1212A	MSD-DIM-CV-12W*	AC180-265V 47-63Hz	12V	1A	12W	94*36*17	100G
45-PS3012A 45-PS3012B	MSD-CV-30W	AC85-265V 50/60Hz	DC12V	2.5A	30W	150*44*32	500g
45-PS4012A 45-PS4012B	MSD-CV-40W	AC85-265V 50/60Hz	DC12V	3.3A	40W	163*56*35	500G
45-PS10012A	MSD-CV-100W	AC85-265V 50/60Hz	DC12V	8.33A	100W	163*56*35	600G
45-PS24012A	MSD-CV-240w	AC85-265V 50/60Hz	DC12V	20A	240W	246*68*39	1.2KG
45-PS40024A	MSD-CV-400w	AC85-265V 50/60Hz	DC24V	16.6A	400W	280*95*50	2.1KG
OPTIONS: A: 1m input lead & AUS plug B: 3m input lead & AUS plug		*12W model NOT IP67					

Geckolighting
Phone: (08) 9248 6205
Email: sales@geckolighting.com.au



www.geckolighting.com.au



geckolighting®
LED