


# Geckolighting® 150w LED Floodlight




## Geckolighting® LED 150w Flood Light

Robust lighting unit with polycarbonate lens (NO GLASS) for outside or inside applications such as open areas, work yards, loading docks and billboards.

**Gecko LED** floodlights deliver long life, high performance and minimum power usage. Suitable for Australian 240VAC power. Standard colour is Cool White (6000-6500K).



Model Number	70-FL150
LED power:	150W
Total power:	150W
Input Voltage	85-265VAC
Frequency Range	50/60Hz
Luminous flux:	>16,500lm
Power Factor(PF)	>0.95
Total Harmonic Distortion ( Thd)	<15%
Inrush Current (typ.)	COLD START 75A(t =570 s measured at 50% I ) at 230VAC
Luminous efficiency:	>110-120lm/w
Light efficiency:	>90%
Operating temperature:	-30°C ~ +55°C
Color Temperature	CW - Cool white: 6,000K NW - Neutral White: 4,500K WW - Warm white: 3,000K
Color Index(CRI)	Ra>85
Light Distribution Curve/Beam Pattern	Rectangular optical spot
Lighting angle:	Horizontal axis 120°, vertical axis 60°
Light Body& Lampshade	Aluminum Alloy And PC
IP Rating:	IP65
Working Life	50,000 Hrs
Dimensions – Width x Height x Depth:	425mm(W) x 325mm(H) x 190mm(D)
Net Weight	8Kgs



Distance	Illuminance at a Distance	
	Center Beam LUX	Beam Width
2.0M	1,268.74 LUX	4.4M 4.7M
4.0M	317.18 LUX	8.7M 9.4M
6.0M	140.97 LUX	13.1M 14.1M
8.0M	79.30 LUX	17.5M 18.8M
10.0M	50.75 LUX	21.8M 23.5M
12.0M	35.24 LUX	26.2M 28.2M

Legend:  
■ Vert. Spread: 95.0°  
■ Horiz. Spread: 99.3°



Geckolighting  
 Phone: (08) 9371 2652  
 Fax: (08) 9371 2444  
 sales@geckolighting.com.au



www.geckolighting.com.au

