

Geckolighting® LED 5w - 150w Floodlight Range

Geckolighting® LED Floodlights. High output LED replacement for standard floodlight applications. They are an ideal replacement for existing commercial and domestic fluorescent fittings. Economical LED technology not only reduces power consumption, but eliminates UV, Mercury and other toxic hazards. Also available in SLIMLINE & Explosion Proof Certified versions. Standard supply colour is Cool White (6000k), and Warm White (3000k). Other colour options, including RGB colour changing, are available on order. 240VAC input standard, DC12/24 available as option.




Model	Power	Lumens (lm)	Weight	Dimensions (mm)	Colour Options
70-FL5	5w	500	0.5kg	115 x 110 x 85	CW/WW
70-FL10	10w	1100	0.5kg	115 x 110 x 85	CW (WW/RGB)
70-FL20	20w	1990	1kg	180 x 140 x 130	CW (WW/RGB)
70-FL30	30w	3400	2kg	225 x 185 x 155	CW (WW/RGB)
70-FL50	50w	4776	3kg	285 x 235 x 150	CW (WW/RGB)
70-FL100	100w	9380	8kg	420 x 325 x 190	CW (WW/RGB)
70-FL150	150w	13500	8.5kg	425 x 325 x 190	CW (WW/RGB)



Geckolighting
Phone: (08) 9248 6205
Email: sales@geckolighting.com.au



www.geckolighting.com.au



geckolighting®
LED