

Geckolighting® 'UFO' LED High Bays



Geckolighting® LED 'UFO' style High Bay Light. Solid structure with aluminium alloy casing gives these lights high anti-shock, anti-moisture, anti-dust and good cooling efficiency. These lights have high quality optics ensuring excellent lighting performance in different application areas with different beam angles available as options. Environmentally friendly with no risk of mercury and lead, no UV or infrared radiation. Easy and secure installation with hanging hook or optional hanging plate.

Model Number	80-HBU150	80-HBU200	80-HBU240
LED power:	150W	200W	240W
LED source Bridgelux LED:	150*1W	200*1W	Phillips SMD 240*1W
Luminous Flux:	18000lm	24000lm	28800lm
Product size (Diameter*height in mm):	Dia310*288H	Dia350*230H	Dia350*230H
Weight:	5kg	6.5kg	6.5kg
Light Body Material:	Aluminum housing & tempered glass		
Total Harmonic Distortion (THD):	<15%		
Driver type:	Meanwell HLG round shape		
Input Voltage:	AC85-305V		
Frequency:	47-63Hz		
Power Factor:	>0.95		
Luminous efficiency:	120-130lm/w		
Light efficiency:	>90%		
Operating temperature:	-30°C ~ +50°C		
Color Temperature:	CW - Cool white: 6,000K NW - Neutral White: 4,500K WW - Warm white: 3,000K		
Color Index(CRI):	Ra>80		
Light Distribution Curve/Beam Pattern:	Round optical spot		
Lighting angle:	60°/90°/120°		
IP Rating:	IP65		
Working Life:	~30,000 Hours		
Wind Resistance index:	12 level		

Geckolighting
 Phone: (08) 9248 6205
 Email: sales@geckolighting.com.au



www.geckolighting.com.au

